

**Straw Crimpers**

<b>CR25 Series</b>	
<b>Description</b>	<b>CR2572</b>
<b>Hitch</b>	Cat. 1 Fits Land Pride Quick Hitch
<b>Working Width</b>	69"
<b>Overall Width</b>	78"
<b>Weight (w/o added weight)</b>	475 lbs.
<b>Height</b>	36 1/2"
<b>Front To Back Length</b>	26"
<b>Number Of Discs</b>	12
<b>Disc Spacing</b>	6 1/2"
<b>Hubs</b>	4 Bolt cast iron
<b>Support Stands</b>	Support stands in all four corners
<b>Water Tank Capacity (gallons per tank)</b>	36 gal.
<b>Full Water Tank Weight (2-tanks)</b>	600 lbs.

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*

**Straw Crimpers**

**CR25 Series**

Features	Benefits
<b>Cat. 1 Hitch</b>	Fits Land Pride Quick Hitch, and stout enough to work with any Cat. 1 tractor.
<b>72" width</b>	Mostly used in wide open spaces, 72" covers a nice width.
<b>Plate steel 'A' frame</b>	Plate steel offers greater strength from natural force applied downward from tractor top link.
<b>Tubular Construction</b>	2 1/2" x 2 1/2" x 3/16" Tubing vs. angle iron offers greater strength as well as gives a better appearance.
<b>Expanded metal in weight tray</b>	Adds safety over blade area, doesn't allow foreign weight object to fall into blade area.
<b>Blades</b>	Blades are blunted just right to crimp the straw and not cut it, as well as disturbing the soil very little.
<b>Blade attachment</b>	Blades are independent of each other allowing for less side load torque on each blade during turns.
<b>Blade hub greasing</b>	Each blade hub has a grease zerk for smooth rotation.
<b>Storage stands</b>	Each corner has a storage stand to aid in off the ground storing, as well as aiding in hooking to the tractor.
<b>Blade spacing</b>	Blades are spaced 6" apart to offer optimum crimping.
<b>Optional Water Tanks</b>	Easily add up to 600 lbs. to the 72" to aid in compacted soil conditions. Can easily reduce weight by draining tank incrementally. Water tanks are safer due to precise fit and fastening vs. stacking inconsistent sized objects and difficulty in uniform fastening.

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*